

**ZARN70130-L-TV**

Needle roller/axial cylindrical roller bearing

Needle roller/axial cylindrical roller bearings  
ZARN...-L, double direction, long shaft  
locating washer

## Technical information



## Your current product variant

Cage	TV	Plastic Cage made from PA66
Locating Feature , bearing outer ring	L	Stepped shaft locating washer extended on one side

## Main Dimensions &amp; Performance Data

d	70 mm	Bore diameter
D	130 mm	Outside diameter
H	103 mm	Hight
C <sub>a</sub>	201.000 N	Basic dynamic load rating, axial
C <sub>0a</sub>	630.000 N	Basic static load rating, axial
C <sub>r</sub>	56.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	119.000 N	Basic static load rating, radial
C <sub>ua</sub>	58.000 N	Fatigue load limit, axial
C <sub>ur</sub>	16.100 N	Fatigue load limit, radial
n <sub>G Oil</sub>	2.400 1/min	Limiting speed for oil lubrication
n <sub>G Grease</sub>	800 1/min	Limiting speed for grease lubrication
M <sub>RL</sub>	4,8 Nm	Bearing friction torque
≈m	4,831 kg	Weight

## Mounting dimensions

D <sub>a max</sub>	116 mm	Maximum diameter of housing shoulder
d <sub>a min</sub>	98 mm	Minimum diameter shaft shoulder



## Dimensions

H <sub>1</sub>	74,5 mm	Height outer ring over wave washer
C	25 mm	Width, outer ring
D <sub>1</sub>	115 mm	Rip diameter shaft washer
D <sub>2</sub>	100 mm	Heeldiameter wave washer long
D <sub>3</sub>	115 mm	Outside diameter wave washer long
B	17,5 mm	Width, inner ring
B <sub>1</sub>	38,5 mm	Width wave washer long
B <sub>2</sub>	18 mm	Width heel wave washer long
r <sub>min</sub>	0,3 mm	Minimum chamfer dimension
r <sub>1 min</sub>	0,6 mm	Minimum chamfer dimension

## Temperature range

T <sub>min</sub>	-30 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.

## Additional information

c <sub>aL</sub>	5.800 N/μm	Rigidity axial
c <sub>kL</sub>	6.000 Nm/mrad	Tilting stiffness
M <sub>m</sub>	77,3 kg*cm <sup>2</sup>	Mass moment of inertia
	1 μm	Axial runout
radial	ZMA70/110	Recommended INA precision locknut for radial locking (not included)
axial	AM70	Recommended INA precision locknut for axial locking (not included)
M <sub>A</sub>	330 Nm	Tightening torque nut
	46.786 N	Required locknut force
	100X120X12	Rotary shaft seal to DIN 3760 (not included)



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed