


**ZARN75155-L-TV**

Needle roller/axial cylindrical roller bearing

Needle roller/axial cylindrical roller bearings
ZARN...-L, double direction, long shaft
locating washer

Technical information



Your current product variant

Cage	TV	Plastic Cage made from PA66
Locating Feature , bearing outer ring	L	Stepped shaft locating washer extended on one side

Main Dimensions & Performance Data

d	75 mm	Bore diameter
D	155 mm	Outside diameter
H	125 mm	Hight
C _a	290.000 N	Basic dynamic load rating, axial
C _{0a}	890.000 N	Basic static load rating, axial
C _r	81.000 N	Basic dynamic load rating, radial
C _{0r}	132.000 N	Basic static load rating, radial
C _{ua}	85.000 N	Fatigue load limit, axial
C _{ur}	19.100 N	Fatigue load limit, radial
n _{G Oil}	2.100 1/min	Limiting speed for oil lubrication
n _{G Grease}	700 1/min	Limiting speed for grease lubrication
M _{RL}	8 Nm	Bearing friction torque
≈m	8,966 kg	Weight

Mounting dimensions

D _{a max}	136 mm	Maximum diameter of housing shoulder
d _{a min}	110 mm	Minimum diameter shaft shoulder



Dimensions

H ₁	90 mm	Height outer ring over wave washer
C	30 mm	Width, outer ring
D ₁	135 mm	Rip diameter shaft washer
D ₂	115 mm	Heeldiameter wave washer long
D ₃	135 mm	Outside diameter wave washer long
B	21 mm	Width, inner ring
B ₁	46 mm	Width wave washer long
B ₂	20 mm	Width heel wave washer long
r _{min}	0,3 mm	Minimum chamfer dimension
r _{1 min}	1 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

c _{aL}	6.600 N/μm	Rigidity axial
c _{kL}	8.500 Nm/mrad	Tilting stiffness
M _m	188 kg*cm ²	Mass moment of inertia
	1 μm	Axial runout
radial	ZMA75/125	Recommended INA precision locknut for radial locking (not included)
axial	AM75	Recommended INA precision locknut for axial locking (not included)
M _A	580 Nm	Tightening torque nut
	72.971 N	Required locknut force
	115X140X12	Rotary shaft seal to DIN 3760 (not included)



Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed