


**VLA200844-N-VSP-ZT** [↗](#)

Slewing ring, 4 point contact bearing, external gear teeth

Slewing ring, 4 point contact bearing, external gear teeth

## Technical information



## Your current product variant

Centering	ZT	Centering on inner and outer ring
Gearing	N	Normalized gear teeth on bearing ring
Preload class	VSP	Bearing with preload

## Main Dimensions &amp; Performance Data

$d_{iZT}$	736 mm	Diameter centring inner ring
	IT8	Diameter centring inner ring tolerance
$h_{fIR}$	12 mm	Height of flange
H	56 mm	Height
$D_a$	950,1 mm	Outside Diameter
$D_{iZT}$	847 mm	Diameter centring outer ring
	IT8	Diameter centring outer ring tolerance
T	4,5 mm	Length centering outer ring
t	12 mm	Length centering inner ring
$h_a$	44,5 mm	Width outer ring
$h_i$	44,5 mm	Height of inner ring
$\approx m$	67,05 kg	Weight



## Dimensions

$D_i$	845,5 mm	Inner diameter outer ring
	0,6 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
$d_a$	842,5 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,6 mm	Outside diameter inner ring lower tolerance
$n_i$	18	Number of fixing holes in inner ring
$L_i$	762 mm	Pitchcircle diameter fixing holes inner ring
$d_B$	18 mm	Fixing bore
$n_a$	18	Number of fixing holes in outer ring
$L_a$	885 mm	Pitchcircle diameter fixing holes outer ring
$d_{Ba}$	M12	Tread fixing bore
$G_i$	20 mm	Thread depth fixing hole
$h_{AIR}$	20 mm	Ring cross section
$F_{r\text{ zul}}$	74.300 N	Max. radial load fixing screws (friction locking)
$d_0$	936 mm	Pitch circle diameter gearing
$m$	8 mm	Modul of gearing
$z$	117	Number of teeth
$F_{z\text{ norm}}$	28.300 N	Max. tooth force root fatigue strenght (at a shock factor of 1,2)
$F_{z\text{ max}}$	42.000 N	Max. tooth force against tooth fracture (at a shock factor of 1,35)

## Temperature range

$T_{\text{min}}$	-25 °C	Operating temperature min.
$T_{\text{max}}$	80 °C	Operating temperature max.



### Calculation factors

$C_a$	180.000 N	Basic dynamic load rating, axial
$C_{0a}$	600.000 N	Basic static load rating, axial
$C_r$	163.000 N	Basic dynamic load rating, radial
$C_{0r}$	224.000 N	Basic static load rating, radial


### Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Moments about all axes



Grease Lubrication



Sealed on both sides



Large bearing