



### VSI200744-N

Slewing ring, 4 point contact bearing, internal gear teeth

Slewing ring, 4 point contact bearing, internal gear teeth

## Technical information



### Your current product variant

Gearing	N	Normalized gear teeth on bearing ring
Radial internal clearance	Standard_SL	Standard radial clearance 0 to 0,3 and axial tilting clearance 0 to 0,53

### Main Dimensions & Performance Data

$d_1$	648 mm	Bore Diameter
T	4,5 mm	Length centering inner ring
H	56 mm	Height
$D_a$	816 mm	Outside Diameter
	-0,6 mm	Outside diameter lower tolerance
	0 mm	Outside diameter upper tolerance
$h_a$	44,5 mm	Width outer ring
$h_i$	44,5 mm	Width inner ring
$\approx m$	58,3 kg	Weight



## Dimensions

$D_i$	745,5 mm	Inner diameter outer ring
	0,6 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
$L_a$	790 mm	Pitchcircle diameter fixing holes outer ring
$n_a$	40	Number of fixing holes in outer ring
$d_B$	14 mm	Fixing bore
$d_a$	742,5 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,6 mm	Outside diameter inner ring lower tolerance
$L_i$	705 mm	Pitchcircle diameter fixing holes inner ring
$d_{Bi}$	M12	Tread fixing bore
$G_i$	20 mm	Thread depth fixing hole
$n_i$	40	Number of fixing holes in inner ring
$F_{r\text{ zul}}$	165.200 N	Max. radial load fixing screws (friction locking)
$m$	6 mm	Modul of gearing
$z$	110	Number of teeth
$d_0$	660 mm	Pitch circle diameter gearing
$F_{z\text{ norm}}$	23.700 N	Max. tooth force root fatigue strenght (at a shock factor of 1,2)
$F_{z\text{ max}}$	35.000 N	Max. tooth force against tooth fracture (at a shock factor of 1,35)

## Temperature range








$T_{\text{min}}$	-25 °C	Operating temperature min.
$T_{\text{max}}$	80 °C	Operating temperature max.



### Calculation factors

$C_a$	171.000 N	Basic dynamic load rating, axial
$C_{0a}$	1.200.000 N	Basic static load rating, axial
$C_r$	155.000 N	Basic dynamic load rating, radial
$C_{0r}$	550.000 N	Basic static load rating, radial

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Moments about all axes
-  Grease Lubrication
-  Sealed on both sides
-  Large bearing