



### VSI201094-N

Slewing ring, 4 point contact bearing, internal gear teeth

Slewing ring, 4 point contact bearing, internal gear teeth

## Technical information



### Your current product variant

Gearing	N	Normalized gear teeth on bearing ring
Radial internal clearance	Standard_SL	Standard radial clearance 0 to 0,3 and axial tilting clearance 0 to 0,53

### Main Dimensions & Performance Data

$d_1$	984 mm	Bore Diameter
T	4,5 mm	Length centering inner ring
H	56 mm	Height
$D_a$	1.166 mm	Outside Diameter
	-0,7 mm	Outside diameter lower tolerance
	0 mm	Outside diameter upper tolerance
$h_a$	44,5 mm	Width outer ring
$h_i$	44,5 mm	Width inner ring
$\approx m$	91 kg	Weight



## Dimensions

$D_i$	1.095,5 mm	Inner diameter outer ring
	0,7 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
$L_a$	1.140 mm	Pitchcircle diameter fixing holes outer ring
$n_a$	48	Number of fixing holes in outer ring
$d_B$	14 mm	Fixing bore
$d_a$	1.092,5 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,7 mm	Outside diameter inner ring lower tolerance
$L_i$	1.055 mm	Pitchcircle diameter fixing holes inner ring
$d_{Bi}$	M12	Tread fixing bore
$G_i$	20 mm	Thread depth fixing hole
$n_i$	48	Number of fixing holes in inner ring
$F_{r\ zul}$	198.200 N	Max. radial load fixing screws (friction locking)
$m$	8 mm	Modul of gearing
$z$	125	Number of teeth
$d_0$	1.000 mm	Pitch circle diameter gearing
$F_{z\ norm}$	31.400 N	Max. tooth force root fatigue strenght (at a shock factor of 1,2)
$F_{z\ max}$	46.700 N	Max. tooth force against tooth fracture (at a shock factor of 1,35)

## Temperature range

$T_{min}$	-25 °C	Operating temperature min.
$T_{max}$	80 °C	Operating temperature max.



### Calculation factors

$C_a$	198.000 N	Basic dynamic load rating, axial
$C_{0a}$	1.770.000 N	Basic static load rating, axial
$C_r$	179.000 N	Basic dynamic load rating, radial
$C_{0r}$	810.000 N	Basic static load rating, radial

### Characteristics




Radial load



Axial load in one direction



Axial load in two directions



Moments about all axes



Grease Lubrication



Sealed on both sides



Large bearing