

**VSU200414-ZT**

Slewing ring, 4 point contact bearing, without gear teeth

Slewing Ring, Four Point contact bearing,  
without gear teeth

## Technical information

**Your current product variant**

Centering	ZT	Centering on inner and outer ring
Radial internal clearance	Standard_SL	Standard radial clearance 0 to 0,3 and axial tilting clearance 0 to 0,53

**Main Dimensions & Performance Data**

$d_i$	342 mm	Inner diameter inner ring
	0 mm	Inner diameter inner ring lower tolerance
	0,5 mm	Inner diameter inner ring upper tolerance
$d_{iZT}$	344 mm	Diameter centring inner ring
	IT8	Diameter centring inner ring tolerance
H	56 mm	Height
$D_a$	486 mm	Outside Diameter
	-0,5 mm	Outside diameter lower tolerance
	0 mm	Outside diameter upper tolerance
$D_{aZT}$	484 mm	Centring diameter outer ring
	-IT8	Diameter centring outer ring tolerance
T	10 mm	Length centering outer ring
t	10 mm	Length centering inner ring
$h_a$	44,5 mm	Width outer ring
$h_i$	44,5 mm	Width inner ring
$\approx m$	32 kg	Weight



## Dimensions

$D_i$	415,5 mm	Inner diameter outer ring
	0,5 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
$d_a$	412,5 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,5 mm	Outside diameter inner ring lower tolerance
$d_B$	14 mm	Fixing bore
$L_a$	460 mm	Pitchcircle diameter fixing holes outer ring
$n_a$	24	Number of fixing holes in outer ring
$L_i$	368 mm	Pitchcircle diameter fixing holes inner ring
$n_i$	24	Number of fixing holes in inner ring
$F_{r\text{zul}}$	76.000 N	Max. radial load fixing screws (friction locking)

## Temperature range

$T_{\text{min}}$	-25 °C	Operating temperature min.
$T_{\text{max}}$	80 °C	Operating temperature max.

## Calculation factors

$C_a$	137.000 N	Basic dynamic load rating, axial
$C_{0a}$	660.000 N	Basic static load rating, axial
$C_r$	124.000 N	Basic dynamic load rating, radial (for radial load only)
$C_{0r}$	305.000 N	Basic static load rating, radial (for radial load only)



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Moments about all axes



Grease Lubrication



Sealed on both sides



Large bearing