



### VSU200844 [↗](#)

Slewing ring, 4 point contact bearing, without gear teeth

Slewing Ring, Four Point contact bearing, without gear teeth

## Technical information



### Your current product variant

Radial internal clearance	Standard_SL	Standard radial clearance 0 to 0,3 and axial tilting clearance 0 to 0,53
---------------------------	-------------	--

### Main Dimensions & Performance Data

$d_i$	772 mm	Inner diameter inner ring
	0 mm	Inner diameter inner ring lower tolerance
	0,6 mm	Inner diameter inner ring upper tolerance
H	56 mm	Height
$D_a$	916 mm	Outside Diameter
	-0,6 mm	Outside diameter lower tolerance
	0 mm	Outside diameter upper tolerance
$h_a$	44,5 mm	Width outer ring
$h_i$	44,5 mm	Width inner ring
$\approx m$	60 kg	Weight



## Dimensions

$D_i$	845,5 mm	Inner diameter outer ring
	0,6 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
$d_a$	842,5 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,6 mm	Outside diameter inner ring lower tolerance
$d_B$	14 mm	Fixing bore
$L_a$	890 mm	Pitchcircle diameter fixing holes outer ring
$n_a$	40	Number of fixing holes in outer ring
$L_i$	798 mm	Pitchcircle diameter fixing holes inner ring
$n_i$	40	Number of fixing holes in inner ring
$F_{r\text{zul}}$	165.200 N	Max. radial load fixing screws (friction locking)

## Temperature range

$T_{\text{min}}$	-25 °C	Operating temperature min.
$T_{\text{max}}$	80 °C	Operating temperature max.

## Calculation factors

$C_a$	180.000 N	Basic dynamic load rating, axial
$C_{0a}$	1.360.000 N	Basic static load rating, axial
$C_r$	163.000 N	Basic dynamic load rating, radial (for radial load only)
$C_{0r}$	620.000 N	Basic static load rating, radial (for radial load only)



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Moments about all axes



Grease Lubrication



Sealed on both sides



Large bearing