





## Dimensions

$h_a$	44,5 mm	Width outer ring
$L_a$	885 mm	Pitchcircle diameter fixing holes outer ring
$n_a$	36	Number of fixing holes in outer ring
$b$	44,5 mm	Width gearing
$m$	8 mm	Modul of gearing
$z$	117	Number of teeth
$d_0$	936 mm	Pitch circle diameter gearing
$F_{z\text{ norm}}$	28.300 N	Max. tooth force root fatigue strenght (at a shock factor of 1,2)
$F_{z\text{ max}}$	42.000 N	Max. tooth force against tooth fracture (at a shock factor of 1,35)
$d_a$	843 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,6 mm	Outside diameter inner ring lower tolerance
$h$	44,5 mm	Height of individual ring
$d_B$	14 mm	Fixing bore
$L_i$	798 mm	Pitchcircle diameter fixing holes inner ring
$n_i$	40	Number of fixing holes in inner ring
	M12	Tread fixing bore
$t_G$	20 mm	Thread depth oil connector
	0,05 mm	Running accuracy A (related to the raceway)
	0,05 mm	Running accuracy B (related to the raceway)
	0,09 mm	Running accuracy C (related to the raceway)
	0,08 mm	Running accuracy D (related to the raceway)

## Temperature range








$T_{\text{min}}$	-25 °C	Operating temperature min.
$T_{\text{max}}$	80 °C	Operating temperature max.



### Calculation factors

$C_a$	295.000 N	Basic dynamic load rating, axial
$C_{0a}$	1.110.000 N	Basic static load rating, axial
$C_r$	210.000 N	Basic dynamic load rating, radial (for radial load only)
$C_{0r}$	540.000 N	Basic static load rating, radial (for radial load only)
VSP max	0,04 mm	Maximum bearing preload
VSP min	0,01 mm	Min. bearing preload
$F_{r\text{ zul}}$	148.700 N	Max. radial load fixing screws (friction locking)

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Moments about all axes
-  Grease Lubrication
-  Sealed on both sides
-  Large bearing