



Dimensions

D_i	415 mm	Inner diameter outer ring
	0,5 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
h_a	44,5 mm	Height outer ring
L_a	460 mm	Pitchcircle diameter fixing holes outer ring
n_a	24	Number of fixing holes in outer ring
d_a	413 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,5 mm	Outside diameter inner ring lower tolerance
h_i	44,5 mm	Height of inner ring
d_B	14 mm	Fixing bore
L_i	368 mm	Pitchcircle diameter fixing holes inner ring
n_i	24	Number of fixing holes in inner ring
VSP _{min}	0,01 mm	Min. bearing preload
VSP _{max}	0,03 mm	Maximum bearing preload
	0,04 mm	Running accuracy A (related to the raceway)
	0,04 mm	Running accuracy B (related to the raceway)
	0,06 mm	Running accuracy C (related to the raceway)
	0,06 mm	Running accuracy D (related to the raceway)

Temperature range








T_{min}	-30 °C	Operating temperature min.
T_{max}	80 °C	Operating temperature max.



Calculation factors

C_a	200.000 N	Basic dynamic load rating, axial
C_r	143.000 N	Basic dynamic load rating, radial (for radial load only)
C_{0a}	540.000 N	Basic static load rating, axial
C_{0r}	265.000 N	Basic static load rating, radial (for radial load only)
n_G	92 1/min	Limiting speed
$F_{r zu.}$	99.100 N	Max. radial load screws

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Moments about all axes
-  Grease Lubrication
-  Sealed on both sides
-  Large bearing