

**NUTR40**

## Yoke type track roller

Yoke type track rollers NUTR...-A, double row cylindrical roller bearings with particularly thick-walled outer ring, full complement cylindrical roller set and an inner ring, the outer ring is guided axially by the rolling elements, labyrinth seals on both sides

## Technical information



## Your current product variant

Type of Sealing	2LB	Labyrinth seals on both sides
Outer ring profile	IOP	Optimized INA-profile
Relubrication	IR	Via inner ring

## Main Dimensions &amp; Performance Data

d	40 mm	Bore diameter
D	80 mm	Outside diameter
B	32 mm	Width of the bearing
$C_{r w}$	57.000 N	Basic dynamic load rating, radial
$C_{0 r w}$	80.000 N	Basic static load rating, radial
$C_{u r w}$	11.300 N	Fatigue load limit, radial
$n_{D G}$	1.600 1/min	Speed on permanent grease lubrication
$F_{0 r per}$	60.000 N	Permissible static load, radial
$F_{r per}$	31.000 N	Permissible dynamic load outer ring, radial
$\approx m$	0,816 kg	Weight

## Dimensions

C	30 mm	Width, outer ring
$d_2$	50,5 mm	Stop diameter of thrust washer
$r_{min}$	1,1 mm	Minimum chamfer dimension
$r_1 min$	0,6 mm	Minimum chamfer dimension