

**KR30-X**

## Stud type track roller

Stud type track rollers KR...-B, single row needle roller bearings with particularly thick-walled outer ring, needle roller and cage assembly and a solid roller stud with fixing thread and a mounting aid, axial guidance of outer ring is provided by the contact flange and contact washer, gap seals on both sides, without eccentric collar

## Technical information



## Your current product variant

Sealing	SPSP	Gap seal on both sides
Outer ring profile	X	Cylindrical profile
Grease nipples	2x	Drive-fit lubrication nipple unmounted 2x
Relubrication facility	KSP	Via head, stud and fit
Assembling aid head	I6	Hexagon socket
Assembling aid stud	I6	Hexagon socket

## Main Dimensions &amp; Performance Data

D	30 mm	Outside diameter
d <sub>1</sub>	12 mm	Fit diameter of roller stud / stud
B	40 mm	Width of the roller stud
C <sub>r w</sub>	6.800 N	Basic dynamic load rating, radial
C <sub>0r w</sub>	8.700 N	Basic static load rating, radial
C <sub>ur w</sub>	1.240 N	Fatigue load limit, radial
n <sub>D G</sub>	5.500 1/min	Speed on permanent grease lubrication
≈m	103,4 g	Weight



### Dimensions

B <sub>1</sub>	15,2 mm	Maximum width of thrust washer
B <sub>2</sub>	25 mm	Bolt/stud length effectively
B <sub>3</sub>	6 mm	Distance to lubrication hole
C	14 mm	Width, outer ring
C <sub>1</sub>	0,6 mm	Protrusion outer ring to thrust washer
r <sub>min</sub>	0,6 mm	Minimum chamfer dimension
d <sub>2</sub>	23 mm	Stop diameter of thrust washer
d <sub>3</sub>	3 mm	Diameter lubrication hole
G	M12X1,5	Thread
l <sub>G</sub>	13 mm	Thread length
W	6 mm	Width of flats
R	500 mm	Radius of outer ring outside profile

### Additional information

	NIPA1X4,5	Drive-fit lubrication nipple
M <sub>A</sub>	22 Nm	Tightening torque nut