




## KRV26-PP [↗](#)

### Stud type track roller

Stud type track rollers KRV...-PP-A, single row needle roller bearings with particularly thick-walled outer ring, full complement needle roller set and with a solid roller stud with fixing thread and a mounting aid, axial guidance of outer ring is provided by the plastic axial plain washers, contact flange and contact washer, three-stage sealing by plastic axial plain washer on both sides, without eccentric collar

## Technical information



### Your current product variant

Type of Sealing	PP	Three-stage sealing by plastic axial plain washer on both sides
Outer ring profile	IOP	Optimized INA-profile
Grease nipples	2x	Drive-fit lubrication nipple unmounted 2x
Relubrication	KS	Via head and stud
Assembling aid head	I6	Hexagon socket
Mounting aid	I6	Hexagon socket

### Main Dimensions & Performance Data

D	26 mm	Outside diameter
d <sub>1</sub>	10 mm	Fit diameter of roller stud / stud
B	36 mm	Width
C <sub>r w</sub>	7.300 N	Basic dynamic load rating, radial
C <sub>0r w</sub>	11.600 N	Basic static load rating, radial
C <sub>ur w</sub>	1.520 N	Fatigue load limit, radial
n <sub>D G</sub>	2.600 1/min	Speed on permanent grease lubrication
≈m	55,924 g	Weight







## Dimensions

B <sub>1</sub>	13,2 mm	Width of thrust washer
B <sub>2</sub>	23 mm	Bolt/stud length effectively
C	12 mm	Width, outer ring
C <sub>1</sub>	0,6 mm	Protrusion outer ring to thrust washer
r <sub>min</sub>	0,3 mm	Minimum chamfer dimension
d <sub>2</sub>	17,5 mm	Stop diameter of thrust washer
G	M10X1	Thread
l <sub>G</sub>	12 mm	Thread length
W	5 mm	Width of flats

## Additional information

	NIPA1X4,5	Drive-fit lubrication nipple
M <sub>A</sub>	15 Nm	Tightening torque nut

## Characteristics

-  Radial load
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides