

**PWKR72-2RS-XL**

## Stud type track roller

Stud type track rollers PWKR..-2RS-XL, double row cylindrical roller bearings with particularly thick-walled outer ring, with a central rib, full complement cylindrical roller set and with a solid roller stud with fixing thread and a mounting aid, the outer ring is guided axially by the central rib and rolling elements, protected lip seal on both sides, without eccentric collar, X-life design

X-life

## Technical information



## Your current product variant

Sealing	2RS	Protected lip seal on both sides
Outer ring profile	IOP	Optimized INA-profile
Grease nipples	2x	Drive-fit lubrication nipple unmounted 2x
Relubrication facility	KSP	Via head, stud and fit
Assembling aid head	I6	Hexagon socket
Assembling aid stud	I6	Hexagon socket

## Main Dimensions &amp; Performance Data

D	72 mm	Outside diameter
d <sub>1</sub>	24 mm	Fit diameter of roller stud / stud
B	80 mm	Width
C <sub>r w</sub>	39.000 N	Basic dynamic load rating, radial
C <sub>0r w</sub>	53.000 N	Basic static load rating, radial
C <sub>ur w</sub>	7.100 N	Fatigue load limit, radial
n <sub>D G</sub>	2.200 1/min	Speed on permanent grease lubrication
F <sub>0r per</sub>	53.000 N	Permissible static load, radial
F <sub>r per</sub>	38.500 N	Permissible dynamic load outer ring, radial
≈m	0,969 kg	Weight









## Dimensions

B <sub>1</sub>	30,6 mm	Width of thrust washer
B <sub>2</sub>	49,5 mm	Bolt/stud length effectively
B <sub>3</sub>	11 mm	Distance to lubrication hole
C	28 mm	Width, outer ring
C <sub>1</sub>	1,3 mm	Protrusion outer ring to thrust washer
r <sub>min</sub>	1,1 mm	Minimum chamfer dimension
d <sub>2</sub>	44 mm	Stop diameter of thrust washer
d <sub>3</sub>	4 mm	Diameter lubrication hole
G	M24X1,5	Thread
I <sub>G</sub>	25 mm	Thread length
W	14 mm	Width of flats

## Additional information

	NIPA3X9,5	Drive-fit lubrication nipple
M <sub>A</sub>	220 Nm	Tightening torque nut

## Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides