

**NUKR80** **Stud type track roller**

Stud type track rollers NUKR...-A, double row cylindrical roller bearings with particularly thick-walled outer ring, full complement cylindrical roller set and a solid roller stud with fixing thread and a mounting aid, the outer ring is guided axially by the rolling elements, labyrinth seals on both sides, without eccentric collar

**Technical information****Your current product variant**

Sealing	2LB	Labyrinth seals on both sides
Outer ring profile	IOP	Optimized INA-profile
Grease nipples	2x	Drive-fit lubrication nipple unmounted 2x
Relubrication facility	KSP	Via head, stud and fit
Assembling aid head	I6	Hexagon socket
Assembling aid stud	I6	Hexagon socket

**Main Dimensions & Performance Data**

D	80 mm	Outside diameter
d <sub>1</sub>	30 mm	Fit diameter of roller stud / stud
B	100 mm	Width
C <sub>r w</sub>	71.000 N	Basic dynamic load rating, radial
C <sub>0 r w</sub>	103.000 N	Basic static load rating, radial
C <sub>u r w</sub>	14.400 N	Fatigue load limit, radial
n <sub>D G</sub>	1.800 1/min	Speed on permanent grease lubrication
F <sub>0 r per</sub>	94.000 N	Permissible static load, radial
F <sub>r per</sub>	47.000 N	Permissible dynamic load outer ring, radial
≈m	1,64 kg	Weight



## Dimensions

B <sub>1</sub>	37 mm	Width of thrust washer
B <sub>2</sub>	63 mm	Bolt/stud length effectively
B <sub>3</sub>	15 mm	Distance to lubrication hole
C	35 mm	Width, outer ring
C <sub>1</sub>	1 mm	Protrusion outer ring to thrust washer
r <sub>min</sub>	1,1 mm	Minimum chamfer dimension
d <sub>2</sub>	47 mm	Stop diameter of thrust washer
d <sub>3</sub>	4 mm	Diameter lubrication hole
G	M30X1,5	Thread
I <sub>G</sub>	32 mm	Thread length
W	14 mm	Width of flats

## Additional information

	NIPA3X9,5	Drive-fit lubrication nipple
M <sub>A</sub>	450 Nm	Tightening torque nut

## Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed