

**LR608-2RSR**

## Yoke type track roller

Yoke type track rollers LR6..-2RS/2RSR, single row self-retaining ball bearings with particularly thick-walled outer ring, ball and cage assembly and an inner ring, axial guidance of outer ring is provided by the balls, lip seal on both sides, with axial sealing action/with radial sealing action

## Technical information



## Your current product variant

|                        |         |  |
|------------------------|---------|--|
| Sealing                | 2RSR    | Lip seal on both sides, with radial sealing action |
| Outer ring profile     | R500    | R500   |
| Relubrication facility | Without | Without  |

## Main Dimensions &amp; Performance Data

|           |              |                                       |
|-----------|--------------|---------------------------------------|
| D         | 24 mm        | Outside diameter                      |
| d         | 8 mm         | Bore diameter                         |
| C         | 7 mm         | Height                                |
| $C_{rw}$  | 2.950 N      | Basic dynamic load rating, radial     |
| $C_{0rw}$ | 1.280 N      | Basic static load rating, radial      |
| $C_{urw}$ | 64 N         | Fatigue load limit, radial            |
| $n_{DG}$  | 19.000 1/min | Speed on permanent grease lubrication |
| $m$       | 0,016 kg     | Weight                                |

## Dimensions

|           |        |                                      |
|-----------|--------|--------------------------------------|
| $d_2$     | 10 mm  | Diameter of thrust washer            |
| $r_{min}$ | 0,3 mm | Minimum chamfer dimension            |
| R         | 500 mm | Radius of outer ring outside profile |



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides