

**PASE20-XL-N**

Plummer block housing unit

Plummer block housing units PASE, cast iron housing, radial insert ball bearing with eccentric locking collar, P seals

X-life

Technical information



Your current product variant

| | | |
|----------|----|---|
| Material | GG | Grey cast iron |
| Groove | N | Cast iron housing with undercut slot for end caps |

Main Dimensions & Performance Data

| | | |
|----------------|--------|---------------|
| d | 20 mm | Bore diameter |
| L | 130 mm | Length total |
| H ₂ | 64 mm | Height |
| ≈m | 0,6 kg | Weight |

Mounting dimensions

| | | |
|----------------|---------|----------------------|
| J | 97,5 mm | Distance fixing bore |
| N | 11 mm | Width (slot) |
| N ₁ | 19 mm | Length (slot) |



Dimensions

| | | |
|----------------|---------|---------------------------------------|
| H | 33,3 mm | Distance shaft axis |
| A | 32 mm | Width (base) |
| A ₁ | 19 mm | Width (head) |
| H ₁ | 14,5 mm | Height (base) |
| B ₁ | 31 mm | Locking collar total width |
| S ₁ | 23,5 mm | Distance of raceway to locking collar |
| Q | M6 | Connection thread for lubrication |

Additional information

| | |
|-----------------|---------------------|
| ASE04 | Housing |
| GRAE20-XL-NPP-B | Bearing designation |
| KASK04 | Protecting cap |

Temperature range

| | | |
|------------------|--------|----------------------------|
| T _{min} | -20 °C | Operating temperature min. |
| T _{max} | 120 °C | Operating temperature max. |