

**FAG****UCP213-41** [↗](#)

Plummer block housing unit

Plummer block housing units UCP, cast iron housing, with long base, radial insert ball bearing with grub screws in inner ring, RSR seals

Technical information



Your current product variant

| | | |
|-------------------|----|----------------------|
| Material | GG | Grey cast iron |
| Housing clearance | J7 | Normal swivel torque |

Main Dimensions & Performance Data

| | | |
|-----------------|-----------|-----------------------------------|
| d | 65,088 mm | Bore diameter |
| L | 265 mm | Length total |
| H ₂ | 151 mm | Height |
| C _r | 61.000 N | Basic dynamic load rating, radial |
| C _{0r} | 40.000 N | Basic static load rating, radial |
| C _{ur} | 2.090 N | Fatigue load limit, radial |
| ≈m | 5,55 kg | Weight |

Mounting dimensions

| | | |
|----------------|--------|----------------------|
| J | 203 mm | Distance fixing bore |
| N | 25 mm | Width (slot) |
| N ₁ | 29 mm | Length (slot) |



Dimensions

| | | |
|----------------|---------|---------------------------------------|
| H | 76,2 mm | Distance shaft axis |
| A | 70 mm | Width (base) |
| H ₁ | 27 mm | Height (base) |
| B | 65,1 mm | Width |
| S ₁ | 39,7 mm | Distance of raceway to locking collar |
| Q | M6 | Connection thread for lubrication |

Additional information

| | |
|----------|---------------------|
| P213 | Housing |
| UC213-41 | Bearing designation |

Temperature range

| | | |
|------------------|--------|----------------------------|
| T _{min} | -20 °C | Operating temperature min. |
| T _{max} | 120 °C | Operating temperature max. |