


**PCJT30-XL-N**

Flanged housing unit

Housing units PCJT, two-bolt flanged housing units, cast iron, eccentric locking collar, P seals

X-life

Technical information



Your current product variant

| | | |
|----------|----|---|
| Groove | N | Cast iron housing with undercut slot for end caps |
| Material | GG | Grey cast iron |

Main Dimensions & Performance Data

| | | |
|-------------|----------|-----------------------------------|
| d | 30 mm | Bore diameter |
| L | 80 mm | Flange width |
| H | 142 mm | Height flange |
| U | 46,8 mm | Total height unit |
| C_r | 20.700 N | Basic dynamic load rating, radial |
| C_{0r} | 11.300 N | Basic static load rating, radial |
| C_{ur} | 480 N | Fatigue load limit, radial |
| $\approx m$ | 0,83 kg | Weight |

Mounting dimensions

| | | |
|---|----------|--------------------------|
| J | 116,5 mm | Distance fixing bore |
| N | 11,5 mm | Fixing bore |
| n | 2 | Number of screwing holes |
| W | 4 mm | Width of flats |



Dimensions

| | | |
|----------------|---------|-----------------------------------|
| A | 31 mm | Height housing |
| A ₁ | 12 mm | Thickness of flange |
| A ₂ | 20 mm | Distance raceway |
| B ₁ | 35,8 mm | Locking collar total width |
| V | 80 mm | Shoulder diameter housing |
| Q | M6 | Connection thread for lubrication |
| d ₃ | 44 mm | Outside diameter locking collar |

Additional information

| | |
|-----------------|---------------------|
| GEHCJT06-GG-N | Housing |
| GRAE30-XL-NPP-B | Bearing designation |
| KASK06 | Protecting cap |

Temperature range

| | | |
|------------------|--------|----------------------------|
| T _{min} | -20 °C | Operating temperature min. |
| T _{max} | 100 °C | Operating temperature max. |