

**RMEO35-XL**

Flanged housing unit

Housing units RMEO, four-bolt flanged housing units, cast iron, centring spigot, eccentric locking collar, series 63, R seals

X-life

Technical information



Your current product variant

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	35 mm	Bore diameter
H	174 mm	Height flange
B ₁	51,6 mm	Locking collar total width
U	35,35 mm	Total height unit
C _r	39.000 N	Basic dynamic load rating, radial
C _{0r}	20.900 N	Basic static load rating, radial
C _{ur}	1.090 N	Fatigue load limit, radial
≈m	2,5 kg	Weight

Mounting dimensions

J	141 mm	Pitch circle diameter (holes)
N	19 mm	Fixing bore
Z	100 mm	Diameter spigot
	h8	Diameter spigot clearance
n	4	Number of screwing holes



Dimensions

A	25 mm	Height housing
A ₁	16 mm	Thickness of flange
A ₂	-2 mm	Distance raceway
S	2 mm	Chamfer width
Q	M6	Connection thread for lubrication

Additional information

1	Number of housings
MEO07	Housing
GNE35-XL-KRR-B	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.