

**RCJTY35-TV-VA** [↗](#)

Flanged housing unit

Flanged housing unit RCJTY...-TV-VA

Technical information

Your current product variant

Material	TV	Plastic
----------	----	---------

Main Dimensions & Performance Data

d	35 mm	Bore diameter
L	90 mm	Flange width
H	163 mm	Height flange
U	43,4 mm	Total height unit
C _r	24.600 N	Basic dynamic load rating, radial
C _{0r}	14.600 N	Basic static load rating, radial
C _{ur}	720 N	Fatigue load limit, radial
C _{0r G}	14.900 N	Load carrying capacity (housing)
≈m	0,641 kg	Weight

Mounting dimensions

J	130 mm	Distance fixing bore
N	13 mm	Fixing bore
W	3 mm	Width across flats
n	2	Number of screwing holes



Dimensions

A	32,8 mm	Height housing
A ₁	16,1 mm	Thickness of flange
A ₂	18 mm	Distance raceway
B	42,9 mm	Width

Additional information

1	Number of housings
GEHCJT07-TV	Housing
GYE35-XL-KRR-B-FA107-VA	Bearing designation
KASK07	Protecting cap

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.