

**RCJTY30-XL-N**

## Flanged housing unit

Housing units RCJTY, two-bolt flanged housing units, cast iron, grub screws in inner ring, R seals

X-life

## Technical information



## Your current product variant

Groove	N	Cast iron housing with undercut slot for end caps
Material	GG	Grey cast iron

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
L	80 mm	Flange width
H	142 mm	Height flange
U	42,2 mm	Total height unit
C <sub>r</sub>	19.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	11.300 N	Basic static load rating, radial
C <sub>ur</sub>	480 N	Fatigue load limit, radial
≈m	0,83 kg	Weight

## Mounting dimensions

J	116,5 mm	Distance fixing bore
N	11,5 mm	Fixing bore
n	2	Number of screwing holes



### Dimensions

A	31 mm	Height housing
A <sub>1</sub>	12 mm	Thickness of flange
A <sub>2</sub>	20 mm	Distance raceway
B	38,1 mm	Width
V	80 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication

### Additional information

GEHCJT06-GG-N	Housing
GYE30-XL-KRR-B	Bearing designation
KASK06	Protecting cap

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.