


**PCF30-XL**

## Flanged housing unit

Housing units PCF, four-bolt flanged housing units, cast iron, eccentric locking collar, P seals

X-life

## Technical information



## Your current product variant

Material	GG	Grey cast iron
----------	----	----------------

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
L	108 mm	Flange width
U	40 mm	Total height unit
C <sub>r</sub>	20.700 N	Basic dynamic load rating, radial
C <sub>0r</sub>	11.300 N	Basic static load rating, radial
C <sub>ur</sub>	480 N	Fatigue load limit, radial
≈m	1,01 kg	Weight

## Mounting dimensions

J	82,5 mm	Distance fixing bore
N	11,5 mm	Fixing bore
n	4	Number of screwing holes



### Dimensions

A	22,3 mm	Height housing
A <sub>1</sub>	12 mm	Thickness of flange
A <sub>2</sub>	13,3 mm	Distance raceway
V	85 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication
d <sub>3</sub>	44 mm	Outside diameter locking device

### Additional information

1	Number of housings
CF06	Housing
GRAE30-XL-NPP-B	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.