

**RCJO35-XL**

## Flanged housing unit

Housing units RCJO, four-bolt flanged housing units, cast iron, eccentric locking collar, series 63, R seals

X-life

## Technical information

**Your current product variant**

Material	GG	Grey cast iron
----------	----	----------------

**Main Dimensions & Performance Data**

d	35 mm	Bore diameter
L	135 mm	Flange width
U	53,4 mm	Total height unit
C <sub>r</sub>	39.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	20.900 N	Basic static load rating, radial
C <sub>ur</sub>	1.090 N	Fatigue load limit, radial
≈m	2,55 kg	Weight

**Mounting dimensions**

J	100 mm	Distance fixing bore
N	19 mm	Fixing bore
n	4	Number of screwing holes



### Dimensions

A	31 mm	Height housing
A <sub>1</sub>	16 mm	Thickness of flange
A <sub>2</sub>	20 mm	Distance raceway
V	104 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication
d <sub>3</sub>	55 mm	Outside diameter locking device

### Additional information

1	Number of housings
CJO07	Housing
GNE35-XL-KRR-B	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.