

**RCJO80-XL**

## Flanged housing unit

Housing units RCJO, four-bolt flanged housing units, cast iron, eccentric locking collar, series 63, R seals

X-life

## Technical information



## Your current product variant

Material	GG	Grey cast iron
----------	----	----------------

## Main Dimensions &amp; Performance Data

d	80 mm	Bore diameter
L	250 mm	Flange width
U	109,7 mm	Total height unit
C <sub>r</sub>	123.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	87.000 N	Basic static load rating, radial
C <sub>ur</sub>	4.050 N	Fatigue load limit, radial
≈m	16,5 kg	Weight

## Mounting dimensions

J	196 mm	Distance fixing bore
N	28 mm	Fixing bore
n	4	Number of screwing holes



### Dimensions

A	80 mm	Height housing
A <sub>1</sub>	25 mm	Thickness of flange
A <sub>2</sub>	50 mm	Distance raceway
V	210 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication
d <sub>3</sub>	118 mm	Outside diameter locking device

### Additional information

1	Number of housings
CJO16	Housing
GNE80-XL-KRR-B	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.