



**PCFTR17-XL**

## Flanged housing unit

Housing units PCFTR, three-bolt flanged housing units, cast iron, eccentric locking collar, P seals

X-life

## Technical information

**Your current product variant**

Material	GG	Grey cast iron
----------	----	----------------

**Main Dimensions & Performance Data**

d	17 mm	Bore diameter
H <sub>2</sub>	81 mm	Height flange
U	32,1 mm	Total height unit
C <sub>r</sub>	10.100 N	Basic dynamic load rating, radial
C <sub>0r</sub>	4.750 N	Basic static load rating, radial
≈m	0,43 kg	Weight

**Mounting dimensions**

J	76,1 mm	Pitch circle diameter (holes)
N	11,5 mm	Fixing bore
n	3	Number of screwing holes



### Dimensions

A	20 mm	Height housing
A <sub>1</sub>	11 mm	Thickness of flange
A <sub>2</sub>	10 mm	Distance raceway
H <sub>1</sub>	31 mm	Distance shaft axis
Q	M6	Connection thread for lubrication
d <sub>3</sub>	28,4 mm	Outside diameter eccentric locking collar

### Additional information

1	Number of housings
CFTR03	Housing
GRAE17-XL-NPP-B	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.