



**RRTR35-XL**

## Flanged housing unit

Housing units RRTR, three-bolt flanged housing units, sheet steel, eccentric locking collar, R seals

X-life

## Technical information



## Your current product variant

Material	Steel sheet
----------	-------------

## Main Dimensions &amp; Performance Data

d	35 mm	Bore diameter
H <sub>2</sub>	105,6 mm	Height flange
H	122 mm	Flange width
U	34,8 mm	Total height unit
C <sub>r</sub>	25.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	15.300 N	Basic static load rating, radial
C <sub>0r G</sub>	6.400 N	Load carrying capacity (housing)
≈m	0,78 kg	Weight

## Mounting dimensions

J	100 mm	Distance fixing bore
J	100 mm	Pitch circle diameter (holes)
N	10,5 mm	Fixing square
n	3	Number of screwing holes



### Dimensions

A	9,5 mm	Height housing
H <sub>1</sub>	44,5 mm	Distance shaft axis
S <sub>1</sub>	2,5 mm	Thickness of flange
S	2,5 mm	Thickness of flange
V	81 mm	Shoulder diameter housing

### Additional information

2	Number of housings
FLAN72-MSTR	Housing
E35-XL-KRR-B	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.