

**FAG****UCF212-39** [↗](#)

Flanged housing unit

Flanged housing unit UCF

## Technical information

**Your current product variant**

|          |    |                |
|----------|----|----------------|
| Material | GG | Grey cast iron |
|----------|----|----------------|

**Main Dimensions & Performance Data**

|                 |           |                                   |
|-----------------|-----------|-----------------------------------|
| d               | 61,912 mm | Bore diameter                     |
| L               | 175 mm    | Flange width                      |
| U               | 68,7 mm   | Total height unit                 |
| C <sub>r</sub>  | 56.000 N  | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 36.000 N  | Basic static load rating, radial  |
| C <sub>ur</sub> | 1.870 N   | Fatigue load limit, radial        |
| ≈m              | 4,15 kg   | Weight                            |

**Mounting dimensions**

|                |        |                          |
|----------------|--------|--------------------------|
| J              | 143 mm | Distance fixing bore     |
| N              | 19 mm  | Fixing bore              |
| N <sub>1</sub> | 143 mm | Distance fixing bore     |
| n              | 4      | Number of screwing holes |



### Dimensions

|                |         |                                   |
|----------------|---------|-----------------------------------|
| A              | 48 mm   | Height housing                    |
| A <sub>1</sub> | 20 mm   | Thickness of flange               |
| A <sub>2</sub> | 29 mm   | Distance raceway                  |
| B              | 65,1 mm | Width                             |
| Q              | M6      | Connection thread for lubrication |

### Additional information

|          |                     |
|----------|---------------------|
| 1        | Number of housings  |
| F212     | Housing             |
| UC212-39 | Bearing designation |

### Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |