View product details on medias

26.05.2026, 23:27:17 UTC

SCHAEFFLER

FAG

UCFL202-10

Flanged housing unit

Flanged housing unit UCFL

Technical information





Your current product variant

Material	GG	Grey cast iron

Main Dimensions & Performance Data

d	15,875 mm	Bore diameter
L	60 mm	Flange width
H	113 mm	Height flange
U	33,3 mm	Total height unit
C_r	13.600 N	Basic dynamic load rating, radial
C_{0r}	6.600 N	Basic static load rating, radial
C_{ur}	345 N	Fatigue load limit, radial
≈m	446 g	Weight

Mounting dimensions

J	90 mm	Distance fixing bore
N	12 mm	Fixing bore
n	2	Number of screwing holes

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form

Dimensions

A	25,5 mm	Height housing
A_1	12 mm	Thickness of flange
A_2	15 mm	Distance raceway
B	31 mm	Width
Q	M6	Connection thread for lubrication

Additional information

	1	Number of housings
	FL204	Housing
	UC202-10	Bearing designation

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

The data sheet only contains an overview of the technical data of the selected product. Please refer to the additional documentation for this product. For further information, please use the following link on our website: Contact form