


**FAG****UKFL206** [↗](#)

Flanged housing unit

Flanged housing unit UKFL

## Technical information

**Your current product variant**

Material	GG	Grey cast iron
----------	----	----------------

**Main Dimensions & Performance Data**

d	25 mm	Bore diameter
L	80 mm	Flange width
H	148 mm	Height flange
C <sub>r</sub>	20.700 N	Basic dynamic load rating, radial
C <sub>0r</sub>	11.300 N	Basic static load rating, radial
C <sub>ur</sub>	590 N	Fatigue load limit, radial
≈m	0,94 kg	Weight

**Mounting dimensions**

J	117 mm	Distance fixing bore
N	16 mm	Fixing bore
n	2	Number of screwing holes



### Dimensions

A	31 mm	Height housing
A <sub>1</sub>	14 mm	Thickness of flange
A <sub>2</sub>	18 mm	Distance raceway
B	25 mm	Width
B <sub>1</sub>	38 mm	Locking collar total width
d <sub>3</sub>	45 mm	Outside diameter eccentric locking collar

### Additional information

1	Number of housings
FL206	Housing
UK206	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.