



**FAG****UKFL215** [↗](#)

Flanged housing unit

Flanged housing unit UKFL

## Technical information

**Your current product variant**

Material	GG	Grey cast iron
----------	----	----------------

**Main Dimensions & Performance Data**

d	65 mm	Bore diameter
L	165 mm	Flange width
H	275 mm	Height flange
C <sub>r</sub>	66.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	44.500 N	Basic static load rating, radial
C <sub>ur</sub>	2.300 N	Fatigue load limit, radial
≈m	6,18 kg	Weight

**Mounting dimensions**

J	225 mm	Distance fixing bore
N	23 mm	Fixing bore
n	2	Number of screwing holes



### Dimensions

A	56 mm	Height housing
A <sub>1</sub>	24 mm	Thickness of flange
A <sub>2</sub>	34 mm	Distance raceway
B	44,5 mm	Width
B <sub>1</sub>	73 mm	Locking collar total width
d <sub>3</sub>	98 mm	Outside diameter eccentric locking collar

### Additional information

1	Number of housings
FL215	Housing
UK215	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.