


**FAG****UKT218**

## Take-up housing unit

Housing units UKT, cast iron housing, radial insert ball bearing with adapter sleeve, RSR seals, for linear motion

## Technical information

**Your current product variant**

Material	GG	Grey cast iron
----------	----	----------------

**Main Dimensions & Performance Data**

d	80 mm	Bore diameter
H	215 mm	Height
L	275 mm	Length total
B <sub>1</sub>	86 mm	Locking collar total width
m	12,81 kg	Weight

**Mounting dimensions**

A <sub>1</sub>	28 mm	Width guidance groove
	0,3 mm	Upper width guidance groove tolerance
	0 mm	Lower width guidance groove tolerance
H <sub>1</sub>	190 mm	Distance guidance grooves
	0 mm	Upper distance guidance groove tolerance
	-0,8 mm	Lower distance guidance groove tolerance
N	47 mm	Fixing bore



### Dimensions

L <sub>1</sub>	170 mm	Distance shaft axis
L <sub>2</sub>	30 mm	Length fixed link
L <sub>3</sub>	140 mm	Length guidance groove
A	80 mm	Width housing fixing side
N <sub>1</sub>	40 mm	Width recess
N <sub>2</sub>	80 mm	Height recess
T	130 mm	Height housing fixing side
Q	M6	Connection thread for lubrication
A <sub>2</sub>	55 mm	Width housing

### Additional information

T218	Housing
UK218	Bearing designation

### Temperature range

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.