

**FAG****UCFA209-28**

Take-up housing unit

Housing units UCFA, cast iron housing, radial insert ball bearing with grub screws in inner ring, RSR seals, for swivel motion

Technical information

**Your current product variant**

| | | |
|----------|----|----------------|
| Material | GG | Grey cast iron |
|----------|----|----------------|

Main Dimensions & Performance Data

| | | |
|----|----------|-------------------|
| d | 44,45 mm | Bore diameter |
| L | 181 mm | Length total |
| U | 52,2 mm | Total height unit |
| ≈m | 1,979 kg | Weight |

Mounting dimensions

| | | |
|----------------|--------|----------------------|
| N | 16 mm | Fixing bore |
| N ₁ | 72 mm | Length (slot) |
| N ₂ | 16 mm | Width (slot) |
| J | 148 mm | Distance fixing bore |

Dimensions

| | | |
|----------------|--------|-----------------------------------|
| A ₁ | 18 mm | Thickness of flange |
| A ₂ | 22 mm | Distance raceway |
| A | 38 mm | Height housing |
| V | 108 mm | Shoulder diameter housing |
| W | 90 mm | Width housing slot side |
| Q | M6 | Connection thread for lubrication |



Additional information

| | |
|----------|---------------------|
| FA209 | Housing |
| UC209-28 | Bearing designation |

Temperature range

| | | |
|------------------|--------|----------------------------|
| T _{min} | -20 °C | Operating temperature min. |
| T _{max} | 120 °C | Operating temperature max. |