

**KO.GIHRK60-0860** [↗](#)

## Rod end housing

Hydraulic rod end, with thread clamping device, right hand thread, without plain bearing

## Technical information

**Your current product variant**

Maintenance	Maintenance required
-------------	----------------------

**Main Dimensions & Performance Data**

d <sub>2</sub>	130 mm	Outer eye diameter
D	90 mm	Outside diameter bearing
C <sub>0r</sub>	400.000 N	Basic static load rating, radial
m	4,6 kg	Weight

**Dimensions**

d <sub>3</sub>	M58x1,5	Thread size
d <sub>4</sub>	75 mm	Shank diameter
h <sub>1</sub>	130 mm	Shank Length Internal thread head
C <sub>1 max</sub>	50,5 mm	Width of the rod end, max.
C <sub>1</sub>	49 mm	Width of the rod end
l <sub>7</sub>	65 mm	Distance drilling with/shaft start
l <sub>4</sub>	200 mm	Total length internal thread head
l <sub>3</sub>	59 mm	Thread length Internal thread
d <sub>5</sub>	94 mm	Shank diameter, large



View product details on medias

08.05.2026, 03:17:13 UTC

SCHAEFFLER

### Temperature range

---

T <sub>min</sub>	-60 °C	Operating temperature min.
------------------	--------	----------------------------

T <sub>max</sub>	200 °C	Operating temperature max.
------------------	--------	----------------------------