

**ARCANOL-MULTITOP-25KG** [↗](#)

Bearing grease

Multi-purpose grease ARCANOL-MULTITOP

## Technical information

**Your current product variant**

|                 |       |                       |
|-----------------|-------|-----------------------|
| Grease category | MP    | Multi-purpose greases |
| Package size    | 25 KG | 25 kg hobbock         |

**Technical data**

|                      |                         |                                    |
|----------------------|-------------------------|------------------------------------|
| $\vartheta_{O \min}$ | -50 °C                  | Operating temperature, min.        |
| $\vartheta_{O \max}$ | 140 °C                  | Operating temperature, max.        |
| $\vartheta_G$        | 80 °C                   | Upper continuous limit temperature |
| $n \cdot d_M$        | 800.000 mm/min          | Speed of rotation specific value   |
|                      | Lithium soap            | Thickener type                     |
|                      | Partially synthetic oil | Base oil type                      |
| $v_{40}$             | 82 mm <sup>2</sup> /s   | Base oil viscosity at +40°C        |
| $v_{100}$            | 12,5 mm <sup>2</sup> /s | Base oil viscosity at +100 °C      |
|                      | 2                       | NLGI class                         |
|                      | Multi-purpose grease    | Grease category                    |
| $\rho$               | 0,87 kg/dm <sup>3</sup> | Density                            |
|                      | 25 kg hobbock           | Container                          |
| $\approx m$          | 26,6 kg                 | Weight                             |