



### ARCANOL-VIB3-1KG [🔗](#)

Bearing grease

Special grease ARCANOL-VIB3

## Technical information

### Your current product variant

|                 |      |                 |
|-----------------|------|-----------------|
| Grease category | SG   | Special greases |
| Package size    | 1 KG | 1 kg can        |

### Technical data

|                             |                        |                                    |
|-----------------------------|------------------------|------------------------------------|
| $\vartheta_{O \text{ min}}$ | -30 °C                 | Operating temperature, min.        |
| $\vartheta_{O \text{ max}}$ | 150 °C                 | Operating temperature, max.        |
| $\vartheta_G$               | 90 °C                  | Upper continuous limit temperature |
| $n \cdot d_M$               | 350.000 mm/min         | Speed of rotation specific value   |
|                             | Lithium complex soap   | Thickener type                     |
|                             | Mineral oil            | Base oil type                      |
| $v_{40}$                    | 170 mm <sup>2</sup> /s | Base oil viscosity at +40°C        |
| $v_{100}$                   | 14 mm <sup>2</sup> /s  | Base oil viscosity at +100 °C      |
|                             | 3                      | NLGI class                         |
|                             | Special grease         | Grease category                    |
| $\rho$                      | 0,9 kg/dm <sup>3</sup> | Density                            |
|                             | 1 kg can               | Container                          |
| $\approx m$                 | 1,084 kg               | Weight                             |