



View product details on medias

25.04.2026, 22:47:18 UTC

**SCHAEFFLER**




## **ARCALUB-C2-2P**

Automatic lubricator CONCEPT

CONCEPT2, Multi-point lubricator

Technical information

---



Your current product variant

Drive System	PP	Piston pump
Lubricant volume	V250/300	250/300 cm <sup>3</sup>

Technical data

	Piston pump	Functional principle
V <sub>Lub</sub>	250 cm <sup>3</sup>	Lubricant volume
	0,15 cm <sup>3</sup>	Metering quantity (per outlet and stroke/impulse)
P <sub>op</sub>	30 bar	Operating pressure, max.
	≤ NLGI 2 (suitability test required)	Lubricant
n <sub>pb</sub>	2	Number of pump bodies
n <sub>out</sub>	2	Number of outlets
	≤ 2	Number of lubrication points: direct
	≤ 4	Number of lubrication points: with splitters
	> 4	Number of lubrication points: with progressive distributors
	PA hose	Connection
U <sub>op</sub>	3-V lithium-metal battery	Operating voltage
	microelectronic	Controller (integrated)
	PLC	Controller (extern)
	Integrated, electronic	Monitoring: pressure
	External (PLC)	Monitoring: fill level
	Empty level, back pressure, internal error (PLC)	Error message
	IP54	Protection class
	Polyamide	Housing material
t <sub>min</sub>	-20 °C	Operating temperature, min.
t <sub>max</sub>	70 °C	Operating temperature, max.
	vertical	Mounting position
	91 x 223 x 112	Dimensions (mm)