



View product details on medias

11.06.2026, 08:24:17 UTC

SCHAEFFLER




ARCALUB-C2-2P

Automatic lubricator CONCEPT

CONCEPT2, Multi-point lubricator

Technical information



Your current product variant

Drive System	PP	Piston pump
Lubricant volume	V250/300	250/300 cm ³

Technical data

	Piston pump	Functional principle
V _{Lub}	250 cm ³	Lubricant volume
	0,15 cm ³	Metering quantity (per outlet and stroke/impulse)
P _{op}	30 bar	Operating pressure, max.
	≤ NLGI 2 (suitability test required)	Lubricant
n _{pb}	2	Number of pump bodies
n _{out}	2	Number of outlets
	≤ 2	Number of lubrication points: direct
	≤ 4	Number of lubrication points: with splitters
	> 4	Number of lubrication points: with progressive distributors
	PA hose	Connection
U _{op}	3-V lithium-metal battery	Operating voltage
	microelectronic	Controller (integrated)
	PLC	Controller (extern)
	Integrated, electronic	Monitoring: pressure
	External (PLC)	Monitoring: fill level
	Empty level, back pressure, internal error (PLC)	Error message
	IP54	Protection class
	Polyamide	Housing material
t _{min}	-20 °C	Operating temperature, min.
t _{max}	70 °C	Operating temperature, max.
	vertical	Mounting position
	91 x 223 x 112	Dimensions (mm)