

**HYDNUT395-E** [↗](#)

Hydraulic nut

HYDNUT..-E

## Technical information

**Your current product variant**

|        |   |   |
|--------|---|---|
| Series | E | Metric fine pitch thread/trapezoid thread |
|--------|---|---|

**Technical data**

|                |                       |                      |
|----------------|-----------------------|----------------------|
| d              | Tr395x5               | Thread               |
| D              | 512 mm                | Outer Diameter       |
| B              | 67 mm                 | Width                |
| b              | 56 mm                 | Width press ring     |
| D <sub>1</sub> | 470 mm                |                      |
| d <sub>1</sub> | 397 mm                |                      |
| s              | 17 mm                 | Stroke, max.         |
|                | 356,1 cm <sup>2</sup> | Piston surface       |
|                | 500 bar               | Pressure, max.       |
|                | 1.780 kN              | Drive-up force, max. |
| ≈m             | 44,3 kg               | Weight               |

**Additional information**

|                                 |                |
|---------------------------------|----------------|
| 1 pc. Hydraulic nut,            | Delivery scope |
| 3 pcs. Clamping screws,         |                |
| 1 pc. Screw plug,               |                |
| 1 pc. Connection nipple,        |                |
| 3 pcs. to 5 pcs. Threaded pins, |                |
| 1 pc. Hand lever,               |                |
| 1 pc. Replacement seal set,     |                |
| 1 pc. User manual               |                |