





### VUSZ12044-A

Adjusting gib

## Technical information




### Your current product variant

Size code	12044
Version	A

### Main Dimensions & Performance Data

L	78 mm	Length max
H	16 mm	Height min
B	25 mm	Width
≈m	0,019 kg	Weight



### Mounting dimensions

L <sub>1</sub>	62 mm	
L <sub>2</sub>	73 mm	Max
J <sub>B</sub>	19 mm	
Tol J <sub>B</sub>	+ 0,1 mm	Upper tolerance
Tol J <sub>B</sub>	- 0,1 mm	Lower tolerance
J <sub>L</sub>	25,5 mm	
Tol J <sub>L</sub>	+ 0,1 mm	Upper tolerance
Tol J <sub>L</sub>	- 0,1 mm	Lower tolerance
J <sub>L2</sub>	16,5 mm	
J <sub>L5</sub>	16,5 mm	
Q <sub>1</sub>	7 mm	Max
A <sub>3</sub>	14,2 mm	
N <sub>3</sub>	3,5 mm	
N <sub>4</sub>	12 mm	
T <sub>5</sub>	4 mm	

### Additional information

S <sub>1</sub>	3 mm	Adjustment screw hexagon socket
S <sub>2</sub>	2 mm	Locking/extraction screw hexagon socket
G <sub>3</sub>	M3	Fixing screws DIN ISO4762-12.9
M <sub>A G3</sub>	1,8 Nm	Tightening torque
K <sub>3</sub>	M3	Fixing screws DIN ISO4762-12.9
M <sub>A K3</sub>	1,8 Nm	Tightening torque
D <sub>2</sub>	3,6 mm	Core hole
Δh	0,35 mm	Adjustment max
	0,035 mm	Adjustment per screw revolution



View product details on medias

16.06.2026, 18:07:50 UTC

**SCHAEFFLER**

### Related products

---

PR14044

For linear roller bearing