





VUSZ18059-A

Adjusting gib

Technical information




Your current product variant

Size code	18059
Version	A

Main Dimensions & Performance Data

L	107 mm	Length max
H	25 mm	Height min
B	37,6 mm	Width
≈m	0,632 kg	Weight



Mounting dimensions

L ₁	85 mm	
L ₂	99 mm	Max
J _B	31 mm	
Tol J _B	+ 0,1 mm	Upper tolerance
Tol J _B	- 0,1 mm	Lower tolerance
J _L	38 mm	
Tol J _L	+ 0,1 mm	Upper tolerance
Tol J _L	- 0,1 mm	Lower tolerance
J _{L2}	20,5 mm	
J _{L5}	20 mm	
Q ₁	8 mm	Max
A ₃	22,3 mm	
N ₃	5 mm	
N ₄	16 mm	
T ₅	6 mm	

Additional information

S ₁	6 mm	Adjustment screw hexagon socket
S ₂	3 mm	Locking/extraction screw hexagon socket
G ₃	M4	Fixing screws DIN ISO4762-12.9
M _{A G3}	5 Nm	Tightening torque
K ₃	M4	Fixing screws DIN ISO4762-12.9
M _{A K3}	5 Nm	Tightening torque
D ₂	5 mm	Core hole
Δh	0,4 mm	Adjustment max
	0,05 mm	Adjustment per screw revolution



View product details on medias

27.06.2026, 11:44:37 UTC

SCHAEFFLER

Related products

PR14061

For linear roller bearing