



RUS26086 [↗](#)

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements
RUS..

Technical information



Your current product variant

Size Code 26086

Main Dimensions & Performance Data


| | | |
|------------------|-----------|---------------------------|
| L _{tot} | 90 mm | Total length |
| L | 86,4 mm | |
| B | 40 mm | Width |
| H | 26 mm | Height |
| C | 76.000 N | Basic dynamic load rating |
| C ₀ | 113.000 N | Basic static load rating |
| ≈m | 0,5 kg | Weight |



View product details on medias

04.07.2026, 10:30:14 UTC

SCHAEFFLER



Mounting dimensions

| | | |
|--------------------------|----------|---|
| L ₁ | 52,8 mm | Mounting dimension |
| J _B | 30 mm | Mounting dimension |
| Tol J _B | ± 0,1 mm | Tolerance |
| J _L | 28 mm | |
| Tol J _L | ± 0,1 mm | Tolerance |
| H ₁ | 0,2 mm | |
| L ₄ | 63 mm | Minimum support length |
| L _W | 14 mm | |
| H ₄ | 21 mm | |
| T ₅ | 10,2 mm | |
| G ₁ | M6 | Fixing screws top (DIN ISO 4762-12.9) |
| G1 M _A | 17 Nm | Tightening torque fixing screws |
| K ₃ | M4 | Fixing screws below (DIN ISO 4762-12.9) |
| K3 M _A max | 5 Nm | Tightening torque fixing screws |
| D ₂ | 4,9 mm | |
| | 6 mm | |

Related products

| | |
|--|---------------------|
| VUS26086-A | Adjustment gib |
| UG9741, UGN9741-A, UZ9741, UZN9741-A, UFK4710, UFB6412 | Suitable Guide rail |