



RUS26086 [↗](#)

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements
RUS..

Technical information




Your current product variant

Size code	26086
-----------	-------

Main Dimensions & Performance Data

L _{tot}	90 mm	Total length
L	86,4 mm	
B	40 mm	Width
H	26 mm	Height
C	76.000 N	Basic dynamic load rating
C ₀	113.000 N	Basic static load rating
≈m	0,5 kg	Weight



Mounting dimensions

L ₁	52,8 mm	Mounting dimension
J _B	30 mm	Mounting dimension
Tol J _B	± 0,1 mm	Tolerance
J _L	28 mm	
Tol J _L	± 0,1 mm	Tolerance
H ₁	0,2 mm	
L ₄	63 mm	Minimum support length
L _W	14 mm	
H ₄	21 mm	
T ₅	10,2 mm	
G ₁	M6	Fixing screws top (DIN ISO 4762-12.9)
G1 M _A	17 Nm	Tightening torque fixing screws
K ₃	M4	Fixing screws below (DIN ISO 4762-12.9)
K3 M _A max	5 Nm	Tightening torque fixing screws
D ₂	4,9 mm	
	6 mm	

Related products

VUS26086-A	Adjustment gib
UG9741, UGN9741-A, UZ9741, UZN9741-A, UFK4710, UFB6412	Suitable Guide rail