



### RUS26102 [↗](#)

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements  
RUS..

## Technical information




### Your current product variant

Size code 26102

### Main Dimensions & Performance Data

L <sub>tot</sub>	106 mm	Total length
L	102,4 mm	
B	40 mm	Width
H	26 mm	Height
C	95.000 N	Basic dynamic load rating
C <sub>0</sub>	151.000 N	Basic static load rating
≈m	0,6 kg	Weight



### Mounting dimensions

L <sub>1</sub>	68,9 mm	Mounting dimension
J <sub>B</sub>	30 mm	Mounting dimension
Tol J <sub>B</sub>	± 0,1 mm	Tolerance
J <sub>L</sub>	44 mm	
Tol J <sub>L</sub>	± 0,1 mm	Tolerance
H <sub>1</sub>	0,2 mm	
L <sub>4</sub>	79 mm	Minimum support length
L <sub>W</sub>	14 mm	
H <sub>4</sub>	21 mm	
T <sub>5</sub>	10,2 mm	
G <sub>1</sub>	M6	Fixing screws top (DIN ISO 4762-12.9)
G1 M <sub>A</sub>	17 Nm	Tightening torque fixing screws
K <sub>3</sub>	M4	Fixing screws below (DIN ISO 4762-12.9)
K3 M <sub>A</sub> max	5 Nm	Tightening torque fixing screws
D <sub>2</sub>	4,9 mm	
	6 mm	

### Related products

VUS26102-A	Adjustment gib
UG9741, UGN9741-A, UZ9741, UZN9741-A, UFK4710, UFB6412	Suitable Guide rail