



RUS26126

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements
RUS..

Technical information




Your current product variant

Size code	26126
-----------	-------

Main Dimensions & Performance Data

L _{tot}	130 mm	Total length
L	126,5 mm	
B	40 mm	Width
H	26 mm	Height
C	122.000 N	Basic dynamic load rating
C ₀	209.000 N	Basic static load rating
≈m	0,74 kg	Weight



Mounting dimensions

L 1	93 mm	Mounting dimension
J B	30 mm	Mounting dimension
Tol J B	± 0,1 mm	Tolerance
J L	68 mm	
Tol J L	± 0,1 mm	Tolerance
H 1	0,2 mm	
L 4	103 mm	Minimum support length
L W	14 mm	
H 4	21 mm	
T 5	10,2 mm	
G 1	M6	Fixing screws top (DIN ISO 4762-12.9)
G1 M A	17 Nm	Tightening torque fixing screws
K 3	M4	Fixing screws below (DIN ISO 4762-12.9)
K3 M A max	5 Nm	Tightening torque fixing screws
D 2	4,9 mm	
	6 mm	

Related products

VUS26126-A	Adjustment gib
UG9741, UGN9741-A, UZ9741, UZN9741-A, UFK4710, UFB6412	Suitable Guide rail