

**GE170-SX**

Spherical plain bearing



Angular contact spherical plain bearing,
requiring maintenance, sliding contact
surface: steel/steel, DIN ISO 12240-2, open
design

Technical information



Your current product variant

Maintenance	Maintenance required
Coating	Durotect M Inner- and outer ring coated with Durotect M (Manganese Phosphate)

Main Dimensions & Performance Data

d	170 mm	Inner diameter bearing
D	260 mm	Outside diameter bearing
T	57 mm	Height
C _r	1.420.000 N	Basic dynamic load rating, radial
C _{0r}	5.450.000 N	Basic static load rating, radial
≈m	12,9 kg	Weight

Mounting dimensions

r _{1smin}	3 mm	Edge Spacing
r _{2smin}	1 mm	Edge Spacing
d _{a max}	190,4 mm	Connection measure Inner ring
D _{a min}	208 mm	Housing Connection Diameter
D _{b min}	253 mm	Connection diameter



Dimensions

d_K	250 mm	Ball diameter
D_1	194,3 mm	Inner diameter of housing washer
B	54 mm	Width Inner ring
C	54 mm	Width Outer ring
s	27 mm	Plane Surface Spacing
A	28,5 mm	Distance lubrication Bore
α	1,4 °	Tilt angle
d_{OT}	0 mm	Bore diameter bearing, upper tolerance
d_{UT}	-0,025 mm	Bore diameter bearing, lower tolerance
D_{OT}	0 mm	Outer diameter, upper tolerance
D_{UT}	-0,035 mm	Outside diameter, lower tolerance
T_{OT}	0,35 mm	Height, upper tolerance
T_{UT}	-0,35 mm	Height, lower tolerance
C_{UT}	0 mm	Width outer ring, upper tolerance
C_{OT}	-0,5 mm	Width outer ring, lower tolerance
B_{OT}	0 mm	Width inner ring, upper tolerance
B_{UT}	-0,5 mm	Width inner ring, lower tolerance
d_2	228 mm	Connection measure Inner ring

Temperature range

T_{min}	-60 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.



Characteristics



Radial load



Axial load in one direction



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment