



FAG

**230/530-BEA-XL-MB1-C4** [↗](#)

Spherical Roller Bearing

Spherical roller bearing 230..-BEA-XL-MB1, symmetric 2 outer ribs with rib washer

X-life

## Technical information



## Your current product variant

Design	BEA	With lose center lip ring
Bore type	Z	Cylindrical
Cage	MB1	Solid brass cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication facility	Standard	

## Main Dimensions &amp; Performance Data

d	530 mm	Bore diameter
D	780 mm	Outside diameter
B	185 mm	Width
$C_r$	5.600.000 N	Basic dynamic load rating, radial
$C_{0r}$	10.100.000 N	Basic static load rating, radial
$C_{ur}$	860.000 N	Fatigue load limit, radial
$n_G$	820 1/min	Limiting speed
$n_{gr}$	475 1/min	Reference speed
$\approx m$	304,5 kg	Weight

## Mounting dimensions

$d_{a \min}$	553 mm	Minimum diameter shaft shoulder
$D_{a \max}$	757 mm	Maximum diameter of housing shoulder
$r_{a \max}$	5 mm	Maximum recess radius



### Dimensions

$r_{min}$	6 mm	Minimum chamfer dimension
$D_1$	708 mm	Bore diameter outer ring
$d_s$	12,5 mm	Diameter lubrication hole
$n_s$	23,5 mm	Width of lubricating groove










### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,22	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	3,1	Dynamic axial load factor
$Y_2$	4,62	Dynamic axial load factor
$Y_0$	3,03	Static axial load factor

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment