

**FAG****HCM7005-C-T-P4S-UL-XL**

## High speed spindle bearing

High speed spindle bearing HCM70..-C, adjusted, in pairs or sets, contact angle  $\alpha = 17^\circ$ , with ceramic balls, restricted tolerances

## Technical information



## Your current product variant

Contact angle	Contact angle 17°	Contact angle 17°
Type of Seal	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to DIN 620
Arrangement bearing set	U	Single bearing
Preload	L	Preload light

## Main Dimensions &amp; Performance Data

d	25 mm	Bore diameter
D	47 mm	Outside diameter
B	12 mm	Width
C <sub>r</sub>	8.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	3.150 N	Basic static load rating, radial
C <sub>ur</sub>	250 N	Fatigue load limit, radial
n <sub>G Grease</sub>	56.000 1/min	Limiting speed for grease lubrication
n <sub>G Oil</sub>	85.000 1/min	Limiting speed for oil lubrication
≈m	70 g	Weight



### Mounting dimensions

$d_a$	30 mm	Diameter shaft shoulder
$d_a$	h12	Diameter shaft shoulder clearance
$D_a$	42 mm	Shoulder diameter outer ring
$D_a$	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	0,6 mm	Maximum recess radius
$r_{a1 \max}$	0,3 mm	Maximum recess radius
$E_{tk \min}$	32,7 mm	Minimum diameter injection pitch
$E_{tk \max}$	34,4 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	30,6 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	34,4 mm	Maximum diameter injection pitch
$a$	11,5 mm	Distance between the apexes of the pressure cones

### Dimensions

$r_{\min}$	0,6 mm	Minimum chamfer dimension
$r_{1 \min}$	0,3 mm	Minimum chamfer dimension
$\alpha$	17 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.



### Additional information

$F_{VL}$	24 N	Preload force light
$F_{VM}$	64 N	Preload force medium
$F_{VH}$	133 N	Preload force heavy
$K_{aEL}$	70 N	Lift-off force light
$K_{aEM}$	189 N	Lift-off force medium
$K_{aEH}$	407 N	Lift-off force heavy
$c_{aL}$	24 N/ $\mu$ m	Axial rigidity light
$c_{aM}$	34 N/ $\mu$ m	Axial rigidity medium
$c_{aH}$	46 N/ $\mu$ m	Axial rigidity heavy

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed