

**FAG****HCM7005-C-T-P4S-UL-XL**

High speed spindle bearing

High speed spindle bearing HCM70.-C, adjusted, in pairs or sets, contact angle $\alpha = 17^\circ$, with ceramic balls, restricted tolerances

Technical information

**Your current product variant**

Preload class	L	Preload light
Contact angle	Contact angle 17°	Contact angle 17°
Type of Seal	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	47 mm	Outside diameter
B	12 mm	Width
C_r	8.000 N	Basic dynamic load rating, radial
C_{0r}	3.150 N	Basic static load rating, radial
C_{ur}	250 N	Fatigue load limit, radial
n_G Grease	56.000 1/min	Limiting speed for grease lubrication
n_G Oil	85.000 1/min	Limiting speed for oil lubrication
$\approx m$	70 g	Weight



Mounting dimensions

d_a	30 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	42 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	0,6 mm	Maximum recess radius
$r_{a1 \max}$	0,3 mm	Maximum recess radius
$E_{tk \min}$	32,7 mm	Minimum diameter injection pitch
$E_{tk \max}$	34,4 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	30,6 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	34,4 mm	Maximum diameter injection pitch
a	11,5 mm	Distance between the apexes of the pressure cones

Dimensions

r_{\min}	0,6 mm	Minimum chamfer dimension
$r_{1 \min}$	0,3 mm	Minimum chamfer dimension
α	17 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.



Additional information

F_{VL}	24 N	Preload force light
F_{VM}	64 N	Preload force medium
F_{VH}	133 N	Preload force heavy
K_{aEL}	70 N	Lift-off force light
K_{aEM}	189 N	Lift-off force medium
K_{aEH}	407 N	Lift-off force heavy
c_{aL}	24 N/ μ m	Axial rigidity light
c_{aM}	34 N/ μ m	Axial rigidity medium
c_{aH}	46 N/ μ m	Axial rigidity heavy

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed