


## PAGBA30-PP-AS

Linear plain bearing and housing unit

Linear plain bearing and housing unit; sealed on all sides, with relubrication facility

### Technical information



#### Your current product variant

Size code	30
Seal	PP
Relubrication facility	AS

#### Main Dimensions & Performance Data

F <sub>w</sub>	30 mm	Diameter of ball complement
H	67 mm	Height
L	68 mm	Length
Tol L	h12	Tolerance
B	84 mm	Width
≈m	0,48 kg	Weight



### Mounting dimensions

J <sub>B</sub>	68 mm	
Tol J <sub>B</sub>	+ 0,2 mm	Upper tolerance
Tol J <sub>B</sub>	- 0,2 mm	Lower tolerance
A <sub>5</sub>	42 mm	
Tol A <sub>5</sub>	+ 0,01 mm	Upper tolerance
Tol A <sub>5</sub>	- 0,01 mm	Lower tolerance
L <sub>4</sub>	60 mm	
L <sub>5</sub>	48 mm	
J <sub>L</sub>	45 mm	
Tol J <sub>L</sub>	+ 0,2 mm	Upper tolerance
Tol J <sub>L</sub>	- 0,2 mm	Lower tolerance
H <sub>2</sub>	35 mm	Center height
Tol H <sub>2</sub>	+ 0,01 mm	Upper tolerance
Tol H <sub>2</sub>	- 0,01 mm	Lower tolerance
A <sub>3</sub>	25 mm	
H <sub>6</sub>	8,7 mm	
Tol H <sub>6</sub>	- 0,5 mm	Tolerance
N <sub>1</sub>	6,8 mm	
N <sub>3</sub>	11 mm	
K <sub>5</sub>	M6	
K <sub>8</sub>	NIPA2	Lubrication nipple