




IMAGE  
COMING SOON**KGSNG25-PP-AS**

## Linear Ball Bearing and Housing Unit

Linear ball bearing and housing unit; with self-aligning linear ball bearing, sealed, greased, with relubrication facility

## Technical information



## Your current product variant

Size code	25
Seal	PP
Relubrication facility	AS

## Technical data

	8	Ball rows
≈m	0,63 kg	Weight

## Main Dimensions &amp; Performance Data

F <sub>w</sub>	25 mm	Diameter of ball complement
H	60 mm	Height
B	78 mm	Width
L	58 mm	Length
C <sub>max</sub>	3.950 N	Load capacity dyn.
C <sub>0 max</sub>	4.300 N	Load capacity stat.



### Mounting dimensions

J <sub>B</sub>	60 mm	
Tol J <sub>B</sub>	- 0,15 mm	Upper tolerance
Tol J <sub>B</sub>	+ 0,15 mm	Lower tolerance
B <sub>1</sub>	59,4 mm	
A <sub>5</sub>	39 mm	
Tol A <sub>5</sub>	+ 0,01 mm	Upper tolerance
Tol A <sub>5</sub>	- 0,01 mm	Lower tolerance
J <sub>L</sub>	40 mm	Distance
Tol J <sub>L</sub>	+ 0,15 mm	Upper tolerance
Tol J <sub>L</sub>	- 0,15 mm	Lower tolerance
H <sub>2</sub>	30 mm	Center height
Tol H <sub>2</sub>	+ 0,008 mm	Upper tolerance
Tol H <sub>2</sub>	- 0,016 mm	Lower tolerance
H <sub>4</sub>	41,5 mm	
H <sub>5</sub>	8,3 mm	
T <sub>5</sub>	22 mm	
H <sub>6</sub>	29 mm	
G <sub>2</sub>	M10	
N <sub>1</sub>	8,4 mm	
N <sub>4</sub>	6 mm	
N <sub>3</sub>	15 mm	
K <sub>5</sub>	M8	
K <sub>8</sub>	NIP5MZ	Lubrication nipple